

DHN-54X16/DG/FS

430~440W

Full-Screen Double Glass PV Module

Comprehensive Products & System Certificates

IEC 61215 / IEC 61730 / CE / INMETRO
ISO 45001
2018/International standards for occupational health & safety
ISO 14001
2015/Standards for environmental management system
ISO 9001
2015/Quality management system

 Material & technology warranty

 Linear power output warranty



Frameless design, installable both vertically & horizontally,
No water, no dust, snow slide fast, power generation increased by 6-15%



TOPCon cells double-sided rate up to 85% and
more back power generation by 5-25%



Double-glass Technology,
higher encapsulation blocking and mechanical strength




Higher performance in anti hidden cracking,
acid and alkali, salt spray, water vapor, UV, PID




TOPCon cells, lower attenuation,
better temperature coefficient & dim ligh performance

DHN-54X16/DG/FS 430~440W

Design



30-Year Linear Power Output Warranty



— DAH Solar linear power output guarantee
— Standard linear power output guarantee

Mechanical Specification

No. of Cells	108 (6×18)
Weight	24.1kg
Cells Type	N-type 182×91mm
Dimension (L×W×T)	1722×1134×28mm
Packing	39pcs/pallet, 1014pcs/40HQ

Cable	4.0mm ² , 300/200mm in length, (Including connector) length can be customized
Glass	2.0mm High Transmission, Antireflection Coating
Junction Box	IP68, 3 Bypass Diodes
Connector	MC4 Compatible

Electrical Characteristics

Module Type	DHN-54X16/DG/FS							
	STC		NOCT		STC		NOCT	
Test conditions	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (P _{max} /W)	430	323	435	327	440	331		
Open-circuit Voltage (V _{oc} /V)	38.0	36.10	38.2	36.29	38.4	36.48		
Maximum Power Voltage (V _{mp} /V)	32.5	30.88	32.7	31.07	32.9	31.26		
Short-circuit Current (I _{sc} /A)	13.84	11.17	13.90	11.22	13.96	11.27		
Maximum Power Current (I _{mp} /A)	13.23	10.47	13.30	10.53	13.37	10.59		
Module Efficiency (STC)	22.02%		22.28%		22.53%			
Refer Bifacial Factor			80±5%					

STC-Standard Test Environment: Irradiance 1000W/m², Cell temperature 25°C, Spectrum AM1.5

NOCT-Standard Test Environment: Irradiance 800W/m², Ambient temperature 20°C, Spectrum AM1.5, Wind speed 1m/s

Double-Sided Power Generation Parameters (Rear gain)

Light Intensity	Parameter	Value 1	Value 2	Value 3
5%	Maximum Power (P _{max})	452	457	462
	Module Efficiency (%)	23.12	23.39	23.66
15%	Maximum Power (P _{max})	495	500	506
	Module Efficiency (%)	25.32	25.62	25.91
25%	Maximum Power (P _{max})	538	544	550
	Module Efficiency (%)	27.53	27.85	28.17

Operating Parameters

Maximum System Voltage	1500V DC
Operating Temperature	-40 ~ +85°C
Maximum Series Fuse Rating	30A
Nominal Operating Cell Temperature	45°C±2°C
Application Level	Class A

Temperature Coefficient

Temperature Coefficient of I _{sc} (ΔI _{sc})	0.046%/°C
Temperature Coefficient of V _{oc} (ΔV _{oc})	-0.25%/°C
Temperature Coefficient of P _{max} (ΔP _{mp})	-0.29%/°C
Snow load, frontside / Wind load, backside	5400Pa/2400Pa